



M3 – 5-digit digitales panel meter 96x48 (BxH) Standard signal 0/4-20 mA, 0-10 VDC

- red display of -19999...99999 digits (optional green, orange, blue or tricolour display)
- installation depth: 120 mm without plug-in screw terminal
- multi voltage power supply unit 100-240 VAC, alternatively 10-40 VDC
- adjustment via factory setting or directly on the sensor signal
- min/max-memory with adjustable permanent display
- 30 additional adjustable support points
- display flashing at threshold value exceedance / undercut
- zero key for the triggering of Hold, Tara, display change, setpoint setting, alarm actuation
- flexible alarm system with adjustable delay times
- volume measurement (Totaliser)
- mathematical functions like reciprocal value, square root, square and rounding
- constant setting / setpoint setting
- sliding averaging
- brightness control via parameter or front keys
- programming interlock via access code
- protection class IP65 at the front
- plug-in screw terminal
- optional: 2 or 4 relay outputs or 8 PhotoMos-outputs
- optional: sensor supply
- optional: 1 or 2 independently scalable analog outputs
- optional: galv. isolated digital input for the triggering Tara, Hold, display change
- optional: interface RS232 or RS485
- accessories: pc-based configuration-kit PM-TOOL with CD & USB adapter
- on demand: devices for working temperatures of -20°C...60°C or -40°C...70°C

• **Technical data**

Dimensions	Housing Panel cut-out Fixing Housing material Sealing material Protection type Weight Connection	B96 x H48 x D120 mm, (incl. plug-in terminal D = 139 mm) 92.0 ^{+0.8} x 45.0 ^{+0.6} mm screw elements for insulation thickness up to 15 mm PC Polycarbonate, black EPDM, 65 Shore, black front side IP65 standard, back side IP00 approx. 350 g plug-in terminal; line cross-section up to 2.5 mm ²
Display	Display Digit height Segment colour Range of display Threshold Overflow Underflow Display time	5-digit 14 mm red (standard), optional available in green, blue, orange or tricolour (red/green/orange) -19999 to 99999 optical display flashing horizontal bars at the top horizontal bars at the bottom 0.1 to 10.0 seconds
Measuring input	Span Measuring range Input resistance Measuring fault Temperature drift Measuring time Measuring principle Resolution	-12...12 V / -22...24 mA 0-10 VDC / 0/4-20 mA Ri at ~200 kΩ / Ri at ~100 Ω 0.1% of measuring range, ± 1 digit / 0.1% of measuring range, ± 1 digit 100 ppm/K 0.1 ... 10.0 seconds U/F- conversion approx. 18 bit at 1s measuring time
Output	Relays Switching cycles PhotoMos output Analog output Sensor supply	with change-over contact 250 V / 5 AAC, 30 V / 5 ADC 30 * 10 ⁵ at 5 AAC, 5 ADC contact rate, 10 * 10 ⁶ mechanically Separation in accordance with DIN EN50178 / Specifications in accordance with DIN EN 60255 NOC contacts: 30 VDC/AC, 4 A 0-10 VDC / burden ≥ 10 kΩ, 0/4-20 mA / burden ≤ 500 Ω, 16 bit 24 VDC / 50 mA 10 VDC / 20 mA
Digital input	Input galv. isolated	<2.4 V OFF; >10 V ON; max. 30 VDC, Ri ~ 5 kΩ
Interface	Protocol RS232 RS485	manufacturer's specifics ASCII 9.600 Baud, no parity, 8 DataBit, 1 StopBit, wire length max. 3 m 9.600 Baud, no parity, 8 DataBit, 1 StopBit, wire length max. 1000 m
Power pack	Supply	100-240 VAC 50/60 Hz, DC ±10% (max. 15 VA) 10-40 VDC, galvanic isolated, 18-30 VAC 50/60 Hz (max. 15 VA)
Memory	EEPROM	Data life ≥ 100 years at 25°C
Ambient conditions	Working temperature Storing temperature Climatic density	0 to +60°C -20 to +80°C relative humidity 0-85% on years average without dew
CE-sign EMV	Conformity to directive 2014/30/EU EN 61326, EN 55011	
Safety standard	according to low voltage directive 2014/35/EU EN 61010; EN 60664-1	

Housing:



