

TEMPOMATIC MIX 2 electronic mixer

Ref. 49400615

Battery-operated, Ø 15mm conical inlets




DESCRIPTION

TEMPOMATIC MIX 2 electronic mixer - Ref. 49400615





Deck-mounted electronic basin mixer:
 Independent IP65 electronic control unit.
 Battery-operated with 123 6V Lithium batteries.
 Flow rate pre-set at 4 lpm at 3 bar, adjustable from 1.5 - 6 lpm.
 Scale-resistant flow straightener.
 Adjustable duty flush (pre-set flush ~60 seconds every 24 hours after last use).
 Shock-resistant infrared presence detection sensor.
 Chrome-plated solid brass body.
 PEX flexibles with filters and reduced-stagnation solenoid valves Ø 15mm for compression fittings.
 Fixing reinforced by 2 stainless steel rods.
 Anti-blocking security.
 Side temperature control with adjustable maximum temperature limiter.
 Solenoid valves are upstream of the mixing chamber.
 10-year warranty.

TECHNICAL FEATURES

TEMPOMATIC MIX 2 electronic mixer - Ref. 49400615

Supply	6V battery
Connector	M1/2" Ø 15mm
Technology	Electronic
Drop height	125mm
Spout length	145mm
Flow rate	4 lpm
Warranty	

ADVANTAGES

-  Independent IP65 electronic control unit
-  85% water savings
-  Complete hygiene: no manual contact
-  Duty flush limits bacterial proliferation

